

JTC Import Export Pty Ltd

Chemwatch: 5391-39 Version No: 4.1.1.1 Safety Data Sheet according to WHS and ADG requirements

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier

Product name	Homebright Foaming Bathroom Cleaner
Synonyms	Product Code: 67512
Proper shipping name	AEROSOLS
Other means of identification	Not Available
Relevant identified uses of the substance or mixture and uses advised against	

Relevant identified uses Bathroom and tile cleaner - Aerosol.

Details of the supplier of the safety data sheet

Registered company name	JTC Import Export Pty Ltd
Address	98 South Park Drive Dandenong South VIC 3175 Australia
Telephone	+61 3 9532 5100
Fax	+61 3 9532 6102
Website	http://www.jtcimportexport.com.au
Email	sales@jtcimportexport.com.au

Emergency telephone number

Association / Organisation	JTC Import Export Pty Ltd	
Emergency telephone numbers	+61 3 9532 5100 (Mon-Thurs 8.30am to 5.30pm; Friday 8.30am to 3pm)	
Other emergency telephone numbers	Not Available	

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

Hazard pictogram(s)

Poisons Schedule	Not Applicable	
Classification ^[1]	Skin Sensitizer Category 1, Chronic Aquatic Hazard Category 3	
Legend:	1. Classified by Chernwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI	
abel elements		



	•
SIGNAL WORD	WARNING
Hazard statement(s)	
H317	May cause an allergic skin reaction.
H412	Harmful to aquatic life with long lasting effects.
AUH044	Risk of explosion if heated under confinement.
Precautionary statement(s) Prevention	

P280 Wear protective glo

Wear protective gloves/protective clothing/eye protection/face protection.

Continued...

Chemwatch Hazard Alert Code: 2 Issue Date: 14/02/2020 Print Date: 28/02/2020 S.GHS.AUS.EN

P273 Avoid release to the environment.	
P272 Contaminated work clothing should not be allowed out of the workplace.	

Precautionary statement(s) Response

P321	Specific treatment (see advice on this label).	
P363	Wash contaminated clothing before reuse.	
P302+P352	IF ON SKIN: Wash with plenty of water.	
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.	

Precautionary statement(s) Storage

Not Applicable

Precautionary statement(s) Disposal

P501 Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
6381-92-6	1-5	EDTA disodium salt dihydrate
Not Available	0.1-1	ingredient, proprietary
68476-85-7.	2-10	hydrocarbon propellant

SECTION 4 FIRST AID MEASURES

Description of first aid measures

Eye Contact	 If aerosols come in contact with the eyes: Immediately hold the eyelids apart and flush the eye with fresh running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Seek medical attention without delay; if pain persists or recurs seek medical attention. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If solids or aerosol mists are deposited upon the skin: Flush skin and hair with running water (and soap if available). Remove any adhering solids with industrial skin cleansing cream. DO NOT use solvents. Seek medical attention in the event of irritation.
Inhalation	 If aerosols, fumes or combustion products are inhaled: Remove to fresh air. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. If breathing is shallow or has stopped, ensure clear airway and apply resuscitation, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Transport to hospital, or doctor.
Ingestion	 If swallowed do NOT induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Observe the patient carefully. Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. Seek medical advice.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 FIREFIGHTING MEASURES

Extinguishing media

SMALL FIRE:

► Water spray, dry chemical or CO2 LARGE FIRE:

Water spray or fog.

Special hazards arising from the substrate or mixture

Fire Incompatibility	Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result		
Advice for firefighters			
Fire Fighting	 Alert Fire Brigade and tell them location and nature of hazard. May be violently or explosively reactive. 		

	 Wear breathing apparatus plus protective gloves. Prevent, by any means available, spillage from entering drains or water course. If safe, switch off electrical equipment until vapour fire hazard removed. Use water delivered as a fine spray to control fire and cool adjacent area. DO NOT approach containers suspected to be hot. Cool fire exposed containers with water spray from a protected location. If safe to do so, remove containers from path of fire. Equipment should be thoroughly decontaminated after use.
Fire/Explosion Hazard	 Non combustible. Not considered to be a significant fire risk. Heating may cause expansion or decomposition leading to violent rupture of containers. Aerosol cans may explode on exposure to naked flames. Rupturing containers may rocket and scatter burning materials. Hazards may not be restricted to pressure effects. May emit acrid, poisonous or corrosive fumes. Decomposes on heating and may emit toxic fumes of carbon monoxide (CO). Decomposition may produce toxic fumes of: carbon dioxide (CO2) nitrogen oxides (NOx) other pyrolysis products typical of burning organic material.
HAZCHEM	Not Applicable

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	 Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes. Wear protective clothing, impervious gloves and safety glasses. Shut off all possible sources of ignition and increase ventilation. Wipe up. If safe, damaged cans should be placed in a container outdoors, away from all ignition sources, until pressure has dissipated. Undamaged cans should be gathered and stowed safely.
Major Spills	 Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. May be violently or explosively reactive. Wear breathing apparatus plus protective gloves. Prevent, by any means available, spillage from entering drains or water courses No smoking, naked lights or ignition sources. Increase ventilation. Stop leak if safe to do so. Water spray or fog may be used to disperse / absorb vapour. Absorb or cover spill with sand, earth, inert materials or verniculite. If safe, damaged cans should be placed in a container outdoors, away from ignition sources, until pressure has dissipated. Undamaged cans should be gathered and stowed safely. Collect residues and seal in labelled drums for disposal.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

Safe handling	 Use in a well-ventilated area. Prevent concentration in hollows and sumps. DO NOT enter confined spaces until atmosphere has been checked. Avoid smoking, naked lights or ignition sources. Avoid contact with incompatible materials. When handling, DO NOT eat, drink or smoke. DO NOT incinerate or puncture aerosol cans. DO NOT spray directly on humans, exposed food or food utensils. Avoid clothes should be laundered separately. Use good occupational work practice. Observe manufacturer's storage and handling recommendations contained within this SDS. Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained
Other information	• Keep dry to avoid corrosion of cans. Corrosion may result in container perforation and internal pressure may eject contents of can

Suitable container	 Aerosol dispenser. Check that containers are clearly labelled.
Storage incompatibility	Avoid reaction with oxidising agents

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA		STEL	Peak	Notes
Australia Exposure Standards	hydrocarbon propellant	LPG (liquified petroleum gas)	gas) 1000 ppm / 1800 mg/m3		Not Available	Not Available	Not Available
EMERGENCY LIMITS							
Ingredient	Material name	Material name T		TEEL-1	TEEL-2	Т	EL-3
EDTA disodium salt dihydrate	Ethylenediaminetetraaceti	Ethylenediaminetetraacetic acid, disodium salt		11 mg/m3	120 mg/m3		0 mg/m3
EDTA disodium salt dihydrate	Ethylenediaminetetraaceti	Ethylenediaminetetraacetic acid, disodium salt, dihydrate		30 mg/m3	330 mg/m	3 2,	000 mg/m3
hydrocarbon propellant	Liquified petroleum gas; (L.P.G.)		65,000 ppm	2.30E+05	ppm 4.	00E+05 ppm	
Ingredient	Original IDLH			Revised IDLH			
EDTA disodium salt dihydrate	Not Available	Not Available		Not Available			
hydrocarbon propellant	2,000 ppm N		Not Available				

Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit		
EDTA disodium salt dihydrate	E	≤ 0.01 mg/m³		
Notes:	Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.			

Exposure controls

	Engineering controls are used to remove a hazard or place a be highly effective in protecting workers and will typically be in The basic types of engineering controls are: Process controls which involve changing the way a job activit Enclosure and/or isolation of emission source which keeps a "adds" and "removes" air in the work environment. Ventilation ventilation system must match the particular process and che Employers may need to use multiple types of controls to preve General exhaust is adequate under normal conditions. If risk obtain adequate protection. Provide adequate ventilation in warehouse or closed storage Air contaminants generated in the workplace possess varying circulating air required to effectively remove the contaminant.	ndependent of worker interactions to provide this hi ty or process is done to reduce the risk. selected hazard "physically" away from the worker n can remove or dilute an air contaminant if designe emical or contaminant in use. vent employee overexposure. of overexposure exists, wear SAA approved respira areas. g "escape" velocities which, in turn, determine the "c	gh level of protection. and ventilation that strategically d properly. The design of a tor. Correct fit is essential to	
	Type of Contaminant:		Speed:	
Appropriate engineering	aerosols, (released at low velocity into zone of active gene	ration)	0.5-1 m/s	
controls	direct spray, spray painting in shallow booths, gas discharg	e (active generation into zone of rapid air motion)	1-2.5 m/s (200-500 f/min.)	
	Within each range the appropriate value depends on:			
	Lower end of the range	Upper end of the range		
	1: Room air currents minimal or favourable to capture	1: Disturbing room air currents		
	2: Contaminants of low toxicity or of nuisance value only.	2: Contaminants of high toxicity		
	3: Intermittent, low production.	3: High production, heavy use		
	4: Large hood or large air mass in motion	4: Small hood-local control only		
	Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min.) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.			
Personal protection				
Eye and face protection	No special equipment for minor exposure i.e. when handling small quantities. OTHERWISE: For potentially moderate or heavy exposures: Safety glasses with side shields. NOTE: Contact lenses pose a special hazard; soft lenses may absorb irritants and ALL lenses concentrate them.			
Skin protection	See Hand protection below			
Hands/feet protection	 No special equipment needed when handling small quar OTHERWISE: For potentially moderate exposures: Wear general protective gloves, eg. light weight rubber g For potentially heavy exposures: Wear chemical protective gloves, eg. PVC. and safety for 	loves.		

Body protection	See Other protection below
Other protection	No special equipment needed when handling small quantities. OTHERWISE: • Overalls. • Skin cleansing cream. • Eyewash unit. • Do not spray on hot surfaces.

Respiratory protection

Type AX Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required. Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 5 x ES	Air-line*	AX-2	AX-PAPR-2 ^
up to 10 x ES	-	AX-3	-
10+ x ES	-	Air-line**	-

* - Continuous Flow; ** - Continuous-flow or positive pressure demand

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

Aerosols, in common with most vapours/ mists, should never be used in confined spaces without adequate ventilation. Aerosols, containing agents designed to enhance or mask smell, have triggered allergic reactions in predisposed individuals.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Clear liquid with fresh odour; mixes with water.		
Physical state	Liquid	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Applicable
pH (as supplied)	7	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	Not Applicable	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Applicable	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Applicable	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	 Elevated temperatures. Presence of open flame. Product is considered stable. Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

Inhaled

The vapour is discomforting WARNING:Intentional misuse by concentrating/inhaling contents may be lethal.

Ingestion	Not normally a hazard due to physical form of product. Considered an unlikely route of entry in commercial/industrial environments		
Skin Contact	There is some evidence to suggest that this material can cause inflammation of the skin on contact in some persons. Spray mist may produce discomfort Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.		
Eye	There is some evidence to suggest that this material can cause e	ye irritation and damage in some persons.	
Chronic	Skin contact with the material is more likely to cause a sensitisation reaction in some persons compared to the general population. Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure. WARNING: Aerosol containers may present pressure related hazards.		
	ΤΟΧΙΟΙΤΥ	IRRITATION	
	Dermal (None) LD50: 84615 mg/kg* ^[2]	Not Available	
Homebright Foaming Bathroom Cleaner			
	Inhalation (None) LC50: 115.40 mg/l (dust&mist)* ^[2]		
	Oral (None) LD50: 20190 mg/kg* ^[2]		
	TOXICITY	IRRITATION	
EDTA disodium salt dihydrate	Oral (mouse) LD50: 2050 mg/kg ^[2]	Not Available	
	Oral (rat) LD50: 2000 mg/kg ^[2]		
	ΤΟΧΙΟΙΤΥ	IRRITATION	
hydrocarbon propellant	Not Available	Not Available	
Legend:	1. Value obtained from Europe ECHA Registered Substances - A specified data extracted from RTECS - Register of Toxic Effect o	cute toxicity 2.* Value obtained from manufacturer's SDS. Unless otherwise f chemical Substances	
EDTA DISODIUM SALT DIHYDRATE	involve antibody-mediated immune reactions. The significance of distribution of the substance and the opportunities for contact wit distributed can be a more important allergen than one with strong clinical point of view, substances are noteworthy if they produce 3. Asthma-like symptoms may continue for months or even years at known as reactive airways dysfunction syndrome (RADS) which criteria for diagnosing RADS include the absence of previous ain asthma-like symptoms within minutes to hours of a documented airflow pattern on lung function tests, moderate to severe bronch lymphocytic inflammation, without eosinophilia. RADS (or asthma- the concentration of and duration of exposure to the irritating sub result of exposure due to high concentrations of irritating substar disorder is characterized by difficulty breathing, cough and mucu For ethylendiaminetetraacetic acid (EDTA) and its salts: EDTA is a strong organic acid, with a high affinity for alkaline-ear lad and mercury), resulting in highly stable chelate complexes. To chemical reactions, depending on application. EDTA and its salts are expected to be absorbed by the lungs and skin irritation, and severe eye irritation. The greatest risk in the hi used and required by the body. The binding of divalent and trival. These appear to be responsible for all of the known pharmacolog EDTA and its salts are mostly eliminated through the urine, with 4 Trisodium EDTA has not been found to cause cancer. EDTA and encountered.	ter exposure to the material ends. This may be due to a non-allergic condition can occur after exposure to high levels of highly irritating compound. Main vays disease in a non-atopic individual, with sudden onset of persistent exposure to the irritant. Other criteria for diagnosis of RADS include a reversible al hyperreactivity on methacholine challenge testing, and the lack of minimal b) following an irritating inhalation is an infrequent disorder with rates related to stance. On the other hand, industrial bronchitis is a disorder that occurs as a ce (often particles) and is completely reversible after exposure ceases. The s production. th ions (for example, calcium and magnesium) and heavy-metal ions (such as ne ability of EDTA to complex is used commercially to either promote or inhibit the gastrointestinal tract; absorption through skin is unlikely. They cause mild uman body will occur when the EDTA attempts to scavenge the trace metals ant cations by EDTA can cause mineral deficiencies, such as zinc deficiency.	
HYDROCARBON PROPELLANT	cellular DNA.		
EDTA DISODIUM SALT DIHYDRATE & HYDROCARBON PROPELLANT	No significant acute toxicological data identified in literature sear	ch.	
Acute Toxicity	×	Carcinogenicity X	

× Reproductivity X Skin Irritation/Corrosion Serious Eye Damage/Irritation × STOT - Single Exposure × Respiratory or Skin ¥ STOT - Repeated Exposure × sensitisation Mutagenicity × Aspiration Hazard × X − Data either not available or does not fill the criteria for classification
→ − Data available to make classification Legend:

SECTION 12 ECOLOGICAL INFORMATION

Homebright Foaming Bathroom Cleaner	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	Not Available	Not Available	Not Available	Not Available	Not Available
	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	1-592mg/L	2
	EC50	48	Crustacea	140mg/L	2
EDTA disodium salt dihydrate	EC50	72	Algae or other aquatic plants	>1-mg/L	2
	EC10	72	Algae or other aquatic plants	0.7mg/L	2
	NOEC	72	Algae or other aquatic plants	0.39mg/L	2
	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	24.11mg/L	2
hydrocarbon propellant	EC50	96	Algae or other aquatic plants	7.71mg/L	2
	LC50	96	Fish	24.11mg/L	2
	EC50	96	Algae or other aquatic plants	7.71mg/L	2

Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. **DO NOT** discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
EDTA disodium salt dihydrate	LOW	LOW
		2011

Bioaccumulative potential

Ingredient	Bioaccumulation
EDTA disodium salt dihydrate	LOW (LogKOW = -3.8573)

Mobility in soil

Ingredient	Mobility
EDTA disodium salt dihydrate	LOW (KOC = 1046)

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

Product / Packaging disposal	 Consult State Land Waste Management Authority for disposal. Discharge contents of damaged aerosol cans at an approved site. Allow small quantities to evaporate. DO NOT incinerate or puncture aerosol cans. Bury residues and emptied aerosol cans at an approved site.
------------------------------	--

SECTION 14 TRANSPORT INFORMATION

Labels Required

Marine Pollutant	NO
HAZCHEM	Not Applicable

Land transport (ADG)

,			
UN number	1950		
UN proper shipping name	AEROSOLS		
Transport hazard class(es)	Class 2.2 Subrisk Not Applicable		
Packing group	Not Applicable		
Environmental hazard	Not Applicable		

Air transport (ICAO-IATA / DGR)

UN number	1950			
UN proper shipping name	Aerosols, non-flammable			
Transport hazard class(es)	ICAO/IATA Class2.2ICAO / IATA SubriskNot ApplicableERG Code2L			
Packing group	Not Applicable			
Environmental hazard	Not Applicable			
Special precautions for user	Special provisions Cargo Only Packing Instructions Cargo Only Maximum Qty / Pack Passenger and Cargo Packing Instructions Passenger and Cargo Maximum Qty / Pack Passenger and Cargo Limited Quantity Packing Instructions Passenger and Cargo Limited Maximum Qty / Pack		A98 A145 A167 A802 203 150 kg 203 75 kg Y203 30 kg G	

Sea transport (IMDG-Code / GGVSee)

UN number	1950		
UN proper shipping name	AEROSOLS		
Transport hazard class(es)	IMDG Class 2.2 IMDG Subrisk Not Applicable		
Packing group	Not Applicable		
Environmental hazard	Not Applicable		
Special precautions for user	EMS NumberF-D , S-USpecial provisions63 190 277 327 344 381 959Limited Quantities1000 ml		

Transport in bulk according to Annex II of MARPOL and the IBC code Not Applicable

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

EDTA DISODIUM SALT DIHYDRATE IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Inventory of Chemical Substances (AICS)

HYDROCARBON PROPELLANT IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Dangerous Goods Code (ADG Code) - Dangerous Goods List

Australia Dangerous Goods Code (ADG Code) - List of Emergency Action Codes Australia Dangerous Goods Code (ADG Code) - Packing Instruction - Liquefied and Dissolved Gases

Australia Exposure Standards

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals Australia Inventory of Chemical Substances (AICS) Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5 $\,$

Chemical Footprint Project - Chemicals of High Concern List

International Air Transport Association (IATA) Dangerous Goods Regulations International Maritime Dangerous Goods Requirements (IMDG Code) United Nations Recommendations on the Transport of Dangerous Goods Model Regulations

National Inventory Status

National Inventory	Status		
Australia - AICS	Yes		
Canada - DSL	/es		
Canada - NDSL	lo (hydrocarbon propellant; EDTA disodium salt dihydrate)		
China - IECSC			
Europe - EINEC / ELINCS / NLP	es		
Japan - ENCS	26		
Korea - KECI	Yes		
New Zealand - NZIoC	Yes		
Philippines - PICCS	Yes		

USA - TSCA	Yes	
Taiwan - TCSI		
Mexico - INSQ		
Vietnam - NCI		
Russia - ARIPS	/es	
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)	

SECTION 16 OTHER INFORMATION

Revision Date	14/02/2020
Initial Date	12/02/2020

SDS Version Summary

Version	Issue Date	Sections Updated
3.1.1.1	13/02/2020	Fire Fighter (fire/explosion hazard)
4.1.1.1	14/02/2020	Toxicity and Irritation (Toxicity Figure)

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC-TWA: Permissible Concentration-Time Weighted Average PC-STEL: Permissible Concentration-Short Term Exposure Limit IARC: International Agency for Research on Cancer ACGIH: American Conference of Governmental Industrial Hygienists STEL: Short Term Exposure Limit TEEL: Temporary Emergency Exposure Limit_\circ IDLH: Immediately Dangerous to Life or Health Concentrations OSF: Odour Safety Factor NOAEL :No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value BCF: BioConcentration Factors BEI: Biological Exposure Index This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.